

WELL-GUARD® Pump Panels
 Full Voltage Type, Type SS
 Class 8940



Type SSD4030



Type SSE4050

Class 8940 Type SS panels in NEMA 3R enclosures are specifically designed for pumping applications. Extra space is provided for field installation of auxiliary equipment.

- Type S Contactor provided as standard
- Approved for submersible pump applications
- Class 10 MOTOR LOGIC® SSOLR through 200 hp–480 V, 100 hp–240 V, Type SS only
- All prices include a START push button and a HAND-OFF-AUTO selector switch
- Adjustable trip current
- Phase failure sensitive through 200 hp–480 V, 100 hp–240 V, Type SS only
- Ambient temperature compensated
- All devices are UL Listed, and marked “SUITABLE ONLY FOR USE AS SERVICE EQUIPMENT”

3-Pole Polyphase—480 Vac Maximum (50–60 Hz)—Fusible▲

Volts	Maximum Hp Polyphase	Coil Voltage■	Fuse Clip Amperes◆	Type
480	3, 5, 7½, 10 15, 20, 25 30 40, 50 60, 75, 100 150 200	480–60 440–50	30 60 60 100 200 400	SSC4010★ SSD4025★ SSD4030★ SSE4050★ SSF4100★ SSG4200★